

LOXONE

LOXONE

Need Help?

loxone.com/support

Internorm Extension

Loxone Electronics GmbH
Smart Home 1
4154 Kollerschlag
Austria

loxone.com

V160420



Part No: 100232

Technical Specifications

| | |
|-----------------------------------|--|
| Power supply | 9 ... 28VDC |
| Power consumption | typ. 288mW, max. 312mW |
| Power loss at max. load | 312mW |
| Interfaces | <p>I-tec: 868MHz (SRD Band Europe), EU channel 0 max. Power 3.16mW connection with up to 40 Internorm I-tec devices</p> <p>Loxone Link: connection with Miniserver</p> |
| Ambient temperature | -40...70°C / -40...158°F |
| Humidity | max. 95% r. H. (non condensing) |
| Safety rating | IP20 |
| Dimensions | 35.5x88x57mm / 1.4x3.46x2.24" (LxWxH) |
| Maintenance & Cleaning | The device is free of maintenance and may only be cleaned with a dry cloth. |

Power supply & Loxone Link

| | |
|----------------------------------|--|
| Wire cross-section | 0.05 ... 2.5mm ² / AWG30 ... 12 |
| Stripping length | 6 ... 7.5mm / 0.24 ... 0.30" |
| Torque of terminal blocks | 0.5 ... 0.6Nm / 0.37 ... 0.44 lbf ft |
| Temperature resistance | min. 80°C / 176°F for IEC, min. 75°C / 167°F for UL |

Features

Status LED (dual color)



For additional information, declaration of conformity,
visit www.loxone.com/help/internorm-extension

