#### **Technical Specifications**

Power supply	5 30VDC or 2x 1.5V AA batteries
Power consumption	typ. 170mW, max. 1.2W
Power loss	max. 1.2W
Interface	Loxone Air: 868MHz (SRD Band Europe), 4 channels available 915MHz (ISM Band Region 2), 10 channels available max. Power 3.16mW
Ambient temperature	-20 55°C / -4 131°F
Humidity	max. 80% r.H. (non condensing
Push force	min. 70N
Stroke length	6.7mm / 0.27"
Temperature detection range	-40 125°C / -40 257°F; +/- 0.5°C / 0.9°F
Safety rating	IP 20
Dimensions	49x78.8mm / 1.93x3.10" (DxH) with valve adapter 49x72.3mm / 1.93x2.85" (DxH) without valve adapter
Maintenance & Cleaning	This device is free of main- tenance and may only be cleaned with a dry cloth.

### LOXONE

# Need Help?

loxone.com/support

Loxone Electronics GmbH Smart Home 1 4154 Kollerschlag Austria

loxone.com



#### Part No: 100163

## Valve Actuator Air

LOXONE

#### About the product

Loxone Valve Actuator Air offers smart heating and cooling control on a room-by-room basis.

#### Features


- Valve control
- Interchangeable valve adapters (VA80 included)

#### Installation & electrical connection

Mounting of the equipment must be performed by a qualified technician. During mounting and in case of error a separator (at least 4A) must be present to turn off the supply. The separator must be easily accessible and recognizable.

#### Connection

Wire cross-section	0.26 0.34mm² / AWG23 22
Temperature resistance	-40 105°C / -40 221°F
IDC-Technology	The wires of a cable are pressed into a single insulation cutting terminal. This connection technique works without soldering, screwing and stripping.



#### This folder is a part of the product!



For additional information, declaration of confirmity, visit www.loxone.com/help/valve-actuator-air

#### Information

Contains FCC ID: COR-ZWIR4512AC1

This device complies with part 15 of the FCC Rules.

Operation is subject to the following two conditions:

- 1. This device may not cause harmful interference
- 2. This device must accept any interference received,

including interference that may cause undesired operation